

HDPE optical cable protectors




MAT



HDPE -5 - +50°C A1 750 N/20 cm

Single-coated pipes designed to protect optical cables.
Cable protectors there is possible to deliver with inner wall to be lubricated by mineral oil.
For larger volumes different color versions (beyond presented versions), labeling, number of differential stripes, denticular inner surface or inner diameter size (material thickness) can be ordered based on customer needs and specifications.
Shock resistance: N (normal, ČSN EN 61386-24)
Bend resistance: flexible
The protectors are tested under pressure of 1,5 MPa for the time of 1 hour.
The packaging on wooden drums and pallets for unwinding drums is delivered just upon previous order according to the customers's specification.

conf.	description
A...	color: orange
B...	color: red
C...	color: blue
D...	color: green
E...	color: yellow
F...	color: black
K...	color: light grey
L...	color: dark grey
...B	drum
...P	harness, pallet
...S100	package: harness 100 m
...S300	package: harness 300 m



	conf.								dn	di		L
									mm	mm	mm	m
06025	AS100	BS100	CS100	DS100	ES100	FS100	KS100	LS100	25	20	400	100
	AB	BB	CB	DB	EB	FB	KB	LB				1750
06032	AS100	BS100	CS100	DS100	ES100	FS100	KS100	LS100	32	26 / 27	400	100
	AB	BB	CB	DB	EB	FB	KB	LB				1750
06040	AP	BP	CP	DP	EP	FP	KP	LP	40	33 / 34 / 35	400	2000
	AS100	BS100	CS100	DS100	ES100	FS100	KS100	LS100				100
	AS300	BS300	CS300	DS300	ES300	FS300	KS300	LS300				300
	AB	BB	CB	DB	EB	FB	KB	LB				1250
06050	AP	BP	CP	DP	EP	FP	KP	LP	50	41 / 44	500	1250
	AS100	BS100	CS100	DS100	ES100	FS100	KS100	LS100				100