

SAFETY DATA SHEET

Product Name: Lead Acid Battery

Effective Date: 2026-01-01

Compiler: Xio Baoyue

Checker: Lu Wengying

Approver: Dongxueshang

WUXI HUIZHONG POWER CO., LTD

声 明

Statement

1. 本报告无无锡汇众伟业电气有限公司检验检测专用章、二维码无效。

The report is invalid if it is not affixed the dedicated inspection and testing seal of Wuxi Huizhong Power Co., Ltd. and QR Code on it.

2. 本报告复印件无效。

Copies of the report are invalid.

3. 本报告无编制、审核、批准人签字无效。

The report is invalid without the signatures of compiler, checker and approver.

4. 本报告涂改无效。

The report is invalid if it is forged or altered.

5. 本报告中的检验结论仅适用于收到的样品。

The inspection conclusion of this report only applies to the sample as received.

6. 除另有说明,检测检验类别都是指委托分析。

Unless noted otherwise, the test type is consignment test.

地址: 无锡汇众伟业电气有限公司

Address: 67-2-301 Zhujiang Road, Wangzhuang Street, Xinwu District, Wuxi

City, Jiangsu Province. China.

邮政编码(Post Code):214000

电话(Tel): (0510) 81813146

网址(web site): www.huizhongpower.com

WUXI HUIZHONG POWER CO.,LTD

SAFETY DATA SHEET

LEAD ACID BATTERY

SECTION 1 IDENTIFICATION

Product name: LEAD ACID BATTERY

Company: WUXI HUIZHONG POWER CO.,LTD

Address: 67-2-301 Zhujiang Road, Wangzhuang Street, Xinwu District, Wuxi City,
Jiangsu Province. China.

E-mail: felix@batt123.com

Emergency Phone: 0510-81813146

Recommend use of the chemical and restrictions on use:

SDS Number: 262590100397

Effective Date: 2026-01-01

SECTION 2 HAZARDS IDENTIFICATION

The product is outside of the scope of GHS system.

Main Hazards:

Fire or Explosion Hazards:

May decompose when heated and generate corrosive and/or toxic fumes.

Health Hazards:

The internal battery materials are corrosive to the eyes, skin, mucous membranes

and upper respiratory tract. Cause burns. Avoid directly contact with the internal battery. Prevent inhalation.

Environmental Hazards:

The internal battery materials may be harmful to the environment, and attention should be paid to water bodies.

SECTION 3 INFORMATION ON INGREDIENTS

Product name : LEAD ACID BATTERY

Ingredient	Concentration (%)	CAS NO.	EC NO.
LEAD	35	7439-92-1	231-100-4
Lead dioxide	30	1309-60-0	215-174-5
Sulfuric acid	15	7664-93-9	231-639-5
Water	12	7732-18-5	231-791-2
ABS	8	9003-56-9	618-371-8

SECTION 4 FIRST-AID MEASURES

Skin Exposure:

If the internal battery's materials of an opened battery cell come into contact with the skin, remove the contaminated clothing and footwear, immediately flush with plenty of water for at least 20 minutes. Call a physician.

Eye Exposure:

In case of the internal battery's materials in contact with eyes, lift your eyelids immediately and rinse them with running water for more than 20 minutes. Call a physician.

Inhalation Exposure:

If inhaled the internal battery's materials, immediately remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician.

Oral Exposure:

If swallowed the internal battery's materials, do not induce vomiting. If the staff is awake, drink enough warm water or milk. Call a physician.

Most Important Symptoms/Effects, Acute and Delayed:

No data available.

Indication of Immediate Medical Attention and Special Treatment Needed, if

Necessary: No data available.

SECTION 5 FIRE FIGHTING MEASURES

Suitable Extinguishing Media:

Small Fire: Dry chemical, CO₂ or water spray.

Large Fire: Dry chemical, CO₂, alcohol-resistant foam or water spray.

Specific Hazards Arising from the Chemical:

May decompose upon combustion to generate irritating, corrosive or toxic fumes when heated.

Special Protective Action for Fire-fighters:

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Fire-extinguishing work is done from the windward. Uninvolved persons should evacuate to a safe place.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures:

Use personal protective equipment. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Entry to noninvolved personnel should be controlled around the leakage area by roping off. Remove all sources of ignition.

Environmental Precautions:

Avoid leakage to get into the earth, ditches or waters. Avoid directly release the cleaning waste water into the environment.

Methods and Materials for Containment and Cleaning up:

In case of internal materials leak, use dry soil, dry sand or other non-combustible materials to absorb and cover the leakage. Sweep up with spade and transfer to a dry, clean, lidded container for disposal. Avoid raising dust. Ventilate area and wash spill site after material pickup is complete.

SECTION 7 HANDLING AND STORAGE

Precautions for Safe Handling:

Operators should be trained and strictly abide by operating procedures. Wear chemical-resistant protective clothing, chemical-resistant protective gloves and a filter gas mask. Keep away from ignition sources, heat and flame. No smoking at working site. Handling is performed in a well ventilated place. Avoid disassembling the battery at will, reversing battery polarity within the battery assembly and overcharging. Such batteries must be packed in inner packaging in such a manner as to effectively prevent short circuits and to prevent movement which could lead

to short circuits. In case of leakage of the material in the battery, avoid directly contact with eyes and skin. Avoid inhalation. Incompatibilities: Combustible materials, organic chemicals, reducing agents, metals, strong oxidizing agents, bases and water.

Conditions for Safe Storage, Including Any Incompatibilities:

Store in a cool, dry, and well-ventilated area. Keep away from ignition sources, heat and flame. Incompatibilities: Combustible materials, organic chemicals, reducing agents, metals, strong oxidizing agents, bases and water. Such batteries must be packed in inner packaging in such a manner as to effectively prevent short circuits and to prevent movement which could lead to short circuits. Storage place should be equipped with appropriate varieties and quantities of fire fighting equipment and leakage emergency treatment equipment.

SECTION 8 EXPOSURE CONTROL / PPE

Control Parameters:

GBZ 2.1-2019 Occupational Exposure Limits for Hazardous Agents in the Workplace

Part 1: Lead and inorganic Compounds, as Pb Lead dust PC-TWA 0.05 mg/m³

Lead fume PC-TWA 0.03 mg/m³ Remarks G2B (Lead), G2A (Inorganic compounds of lead)

Sulfuric acid PC-TWA 1mg/m³ PC-STEL 2mg/m³ Remarks G1

ACGIH:

Lead and inorganic compounds TLV-TWA 0.05 mg/m³

Sulfuric acid TLV-TWA 0.2 mg/m³, T

Appropriate Engineering Controls:

Mechanical exhaust required. Safety shower and eye bath.

Individual Protection Measures:**Eye/Face Protection:**

Wear chemical safety glasses.

Skin Protection:

Hand Protection: Wear chemical-resistant protective gloves.

Body Protection: Wear chemical-resistant protective clothing.

Respiratory Protection:

Wear a filter gas mask when you may be exposed to electrolyte fumes.

Thermal Hazards:

No data available.

Other Protect:

No smoking, drinking and eating at working site. Wash thoroughly after handling.

SECTION 9 PHYSICAL/CHEMICAL PROPERTIES

Appearance: Grey white Plastics cement shell

Odor: Odorless

pH Value: 1-2

Solubility: partial soluble in water

Melting Point/Freezing > 300°C Point

Boiling Point, Initial No data available.

Boiling Point and

Boiling Range:

Flash Point (Closed Cup): No data available.

Density/Relative Density: No data available.

Kinematic Viscosity: No data available.

Lower/Upper Explosion Limit/Flammability Limit: No data available.

Vapour Pressure: No data available.

Relative Vapor Density: No data available.

N-Octanol/Water (Log Value): No data available.

Autoignition Temperature: No data available.

Decomposition Temperature: No data available.

Particle Characteristics: No data available.

Flammability (Solid , Gas): No data available.

SECTION 10 STABILITY AND REACTIVITY

Reactivity: No data available.

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of Hazardous Reactions: No data available.

Conditions to Avoid: Avoid misoperation, exposure to heat and open flame. Avoid mechanical or electrical abuse and overcharge. Prevent short circuits. Prevent movement which could lead to short circuits.

Incompatible Materials: Combustible materials, organic chemicals, reducing agents, metals, strong oxidizing agents, bases and water.

Hazardous Decomposition Products: Metal oxides, sulfur oxides, sulfuric acid mist,

etc.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Toxicity: No data available.

Skin Corrosion/Irritation: The electrolyte in the battery causes severe skin burns.

Serious Eye Damage/Irritation: The electrolyte in the battery causes serious eye damage.

Respiratory Sensitization: No data available.

Carcinogenicity: No data available.

Skin Sensitization: No data available.

Germ Cell Mutagenicity: The International Agency on Cancer (IARC) has classified "strong inorganic acid mists containing sulfuric acid" as a category 1 carcinogen (inhalation), a substance that is carcinogenic to humans. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist at high levels.

Reproductive Toxicity: No data available.

Specific Target Organ Toxicity - Single Exposure: No data available.

Specific Target Organ Toxicity - Repeated Exposure: No data available.

Aspiration Hazard: No data available.

SECTION 12 ECOLOGICAL INFORMATION

Toxicity: No data available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available.

Other Adverse Effects: No data available.

SECTION 13 DISPOSAL CONSIDERATION

Disposal Methods:

The discarded battery is listed in hazardous waste in the "Catalogue of Hazardous Waste", Number: HW31, Category: Lead-containing Waste. The disposal of discarded battery shall comply with the requirements of relevant laws, regulations, policies and standards such as the "Law of the People's Republic of China on the Prevention and Control of Environmental Pollution by Solid Waste" and "Technical Policy for the Prevention and Control of Waste Battery Pollution". Contact a licensed professional waste disposal service to dispose of wastes. Used battery being transported for disposal or reclamation should be carefully checked prior to shipment to ensure the integrity of each battery and its suitability for transport.

SECTION 14 TRANSPORT INFORMATION

The battery has passed the vibration test, pressure differential test and leakage test at 55°C according to Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations (23rd) SPECIAL PROVISION 238.

RID/ADR(2025 Edition): The battery is not subject to RID/ADR according to special provision 238.

IATA DGR(66th Edition): The battery is not subject to IATA DGR according to

special provision A67.

IMO IMDG CODE (2022 Edition): The battery is not subject to IMO IMDG CODE according to special provision 238.

SECTION 15 REGULATORY INFORMATION

Domestic Regulations:

The battery has passed the vibration test, pressure differential test and leakage test at 55°C according to Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations (23rd) SPECIAL PROVISION 238.

Regulations Concerning Road Transportation of Dangerous Goods (JT/T 617-2018):

The battery is not subject to JT/T 617-2018 according to special provision 238.

List of Dangerous Goods (GB 12268-2025):

The battery is not subject to GB 12268-2025 according to special provision 238.

List of Dangerous Goods by Rail (TB/T 30006-2022):

The product is not subject to TB/T 30006-2022 according to special provision 77.

International Regulations:

Directive (EU) 2023/1542 and 2013/56/EU:

The label, disposal and recycling of the battery shall meet the requirements of EU Directive (EU) 2023/1542 and 2013/56/EU.

SECTION 16 OTHER INFORMATION

Preparation Date: 2026-01-01

Preparation Department: Wuxi Huizhong Power Co., Ltd.

Tel:+86-510-81813146

Revision: 0

Abbreviations and Acronyms:

- CAS: Chemical Abstracts Service
- EC: European Commission
- ACGIH: American Conference of Governmental Industrial Hygienists
- PC-TWA: Permissible concentration-time weighted average
- PC-STEL: Permissible concentration-short term exposure limit
- TLV-TWA: Threshold limit value-time weighted average
- TLV-STEL: Threshold limit value-short term exposure limit
- G2B: Possibly carcinogenic to humans
- G2A: Probably carcinogenic to humans
- G1: Carcinogenic to humans
- T: Measured as thoracic fraction of the aerosol
- RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IATA DGR: International Air Transport Association Dangerous Goods Regulations
- IMO IMDG CODE: International Maritime Organization International Maritime Code for Dangerous Goods

- EU: European Union

Other Information:

This SDS is only compiled for battery and based on the information such as ingredients provided by the applicant and our current knowledge. This SDS shall be used only as a guide. If the battery is used as a component in another product, the information in this SDS may not be applicable. The users of this SDS must make independent judgments on the correctness and completeness and then decide its suitability according to the actual situation. The users should take the relevant legal responsibilities for the consequences of use.